



BOARD MOUNT PRESSURE SENSORS









TE Connectivity (TE) offers a full line of printed circuit board mount pressure sensors for a wide range of applications and industries where digital or analog output, compact size, lightweight, and cost-effective solutions are needed. Choose the best solution for your application from our broad selection of digital and analog PCB mountable pressure sensors, available in both through-hole and surface mount configurations. Engineered with leading edge MEMS technology and our proven experience in design and manufacturing capabilities—TE pressure sensors provide advanced performance, durability, and long-term stability. Use TE's innovative board mount pressure sensors to enhance your product's performance. Whatever your industry challenge, TE has the solution.

- Digital Output
- Analog Output
- Small Size
- Light Weight
- PCB Mountable
- Through-Hole or Surface Mount










DESIGN QUESTIONS

- What type of pressure reading is needed for the application?
- What pressure accuracy is needed?
- What is the output needed (I²C, analog)?
- What are your environmental conditions, operating temperature and humidity range?
- Are there some environmental constraints such as chemicals, pollution, water immersion; repeated condensation events?

STANDARD SIZE BOARD MOUNT PRESSURE SENSORS



Premium Line Board Mount Pressure Sensors										
	Product Family	Package	Supply Voltage	Pressure Range	Calibrated Temperature [°C]	Output	TEB [%FS]	Size[mm]	Feature	Typical Application
	HCLA	THT / SMT	5V / 3.3 V	2.5 - 75mbar	-25 - 85°C	Analog, I ² C, SPI	N/A	17 x 13	Dual Die Sensors	Air Flow Measurement, HVACR, Medical Devices
	HCE	THT / SMT	5V / 3.3 V	10mbar - 5bar	0 - 85°C	Analog, SPI	0.5%	17 x 13	General Purpose Small Port Sensor	Industrial, Medical
	HDI	THT / SMT	5V / 3.3 V	10mbar - 5bar	0 - 85°C	Analog, I ² C, SPI	0.5%	20 x 12	General Purpose Large Port Sensor	Industrial, Medical
	HM	THT	5V / 3.3 V	2.5mbar - 10bar	-20 - 85°C	Analog, I ² C, SPI	0.75%	14 x 10	Increased Media Compatibility	Industrial, Medical
	MS4515DO	THT / SMT	5V / 3.3 V	2 - 30 inH ₂ O	0 - 60°C	I ² C, SPI	1%	13 x 10	Gel Coating, Low Power	Blocked Filter Detection, Medical Devices
	MS4525DO	THT / SMT	5V / 3.3 V	1 - 150 Psi	-10 - 85°C	I ² C, SPI	1%	13 x 10	Gel Coating, Low Power	Factory Automation, Medical Devices
	MS4515	THT / SMT	5V / 3.3 V	2 - 30 inH ₂ O	0 - 60°C	Analog	1%	13 x 10	Gel Coating, Low Power	Blocked Filter Detection, Medical Devices
	MS4525	THT / SMT	5V / 3.3 V	1 - 150 Psi	-10 - 85°C	Analog	1%	13 x 10	Gel Coating, Low Power	Factory Automation, Medical Devices

DIGITAL OUTPUT BOARD MOUNT PRESSURE SENSORS





24-Bit, Ultra-Low Power, Pressure and Temperature Sensors										
	Product	Package	Supply Voltage	Pressure Range	Operating Temperature [°C]	Resolution [mbar]	Accuracy [mbar]	Digital Interface Protocol	Size [mm]	Typical Applications
Absolute										
	MS5607-02BA	SMD	1.8 - 3.6 V	10 to 2000 mbar	-40 to +85°C	0.024	±1.5	I ² C or SPI pin selectable	5 x 3 x 1	Mobile Altimeter/Barometer Systems, Bike Computers, Variometers, Dataloggers, Mobile Phones
	MS5611-01BA	SMD	1.8 - 3.6 V	10 to 1200 mbar	-40 to +85°C	0.012	±1.5	I ² C or SPI pin selectable	5 x 3 x 1	Mobile Altimeter/Barometer Systems, Bike Computers, Variometers, Medical Alarms, Indoor Navigation
	MS5637x	SMD	1.5 - 3.6 V	2, 30 bar	-40 to +85°C, -20 to +85°C	0.016, 0.27	±4.0, ±1.5	I ² C	3 x 3 x 0.9	Smart Phones, Tablets, Industrial Equipment, Tire Pressure Monitoring Systems (TPMS)
Absolute										
	MS5849-30BA		1.5 - 3.6 V	0.3Bar to 30 Bar	-40 to +110°C	0.14, 0.19, 0.27, 0.38, 0.55, 0.79, 1.31	+/- 175mbar	I ² C and SPI	3.3 x 3.3 x 2.7	Drones, Fitness Trackers, Bike Computers Mobile Altimeter/Barometer Systems, Wearables, TPMS
	MS5803x	SMD	1.8 - 3.6 V	1, 2, 5, 7, 14, 30 bar	-40 to +85°C	0.012, 0.024, 0.036, 0.04, 0.2, 0.5	±2.5, ±120, ±50, -200 to +100, ±400	I ² C or SPI pin selectable	6.2 x 6.4 x 2.9	Multifunction Watches, Bike Computers, Diving Watches
	MS5805-02BA	SMD	1.8 - 3.6 V	2 bar	-40 to +85°C	0.02	±4.0	I ² C	4.5 x 4.5 x 3.5	Mobile Altimeter/Barometer Systems, Multifunction Watches, Bike Computers, Variometers, Dataloggers
	MS5837x	SMD	1.5 - 3.6 V	2, 7, 30 bar	-20 to +85°C	0.016, 0.2	±4, ±400	I ² C	3.3 x 3.3 x 2.75	Drones, Fitness Trackers, Bike Computers Mobile Altimeter/Barometer Systems, Wearables
	MS5839-02BA	SMD	1.5 - 3.6 V	2 bar	-20 to +85°C	0.016	±4	I ² C	3.3 x 3.3 x 2.75	Shallow Diving Computers, Underwater Drones, Swim Watches, Fitness Trackers, Diving Equipment
	MS5840-02BA	SMD	1.5 - 3.6 V	2 bar	-20 to +85°C	0.016	±4	I ² C	3.3 x 3.3 x 1.7	Drones, Fitness Trackers, Bike Computers Mobile Altimeter/Barometer Systems, Wearables Shallow Diving Computers, Swim Watches
Absolute, Differential, Gauge										
	MS5525DSO	SOIC-14	1.8 - 3.6 V	1, 2, 5, 15, 30 Psi	-40 to +125°C	TEB = ±2.5% FS	±0.25% FS	I ² C or SPI pin selectable	12.5 x 7.9	Factory Automation, Altitude Measurement, Medical Devices

DIGITAL OUTPUT BOARD MOUNT PRESSURE SENSORS

14-Bit, Pressure and Temperature (11-Bit) Sensor





	Product	Package	Supply Voltage	Pressure Range	Operating Temperature [°C]	Total Error [%FS]	Accuracy [%FS]	Digital Interface Protocol	Size [mm]	Typical Applications
	Differential, Gauge									
	MS4515DO	8-pin DIL	3.3 or 5.0 V	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85°C	±1.0	±0.25	I ² C or SPI pin selectable	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
	MS4525DO	8-pin DIL	3.3 or 5.0 V	1, 5, 15, 30, 50, 100, 150 psi	-25 to +105°C	±1.0	±0.25	I ² C or SPI pin selectable	12.45 x 9.90	Factory Automation, Medical Instruments

16-Bit, Ultra-Low Power, Pressure Sensor



	Product	Package	Supply Voltage	Pressure Range	Operating Temperature [°C]	Resolution [mbar]	Accuracy [mbar]	Digital Interface Protocol	Size [mm]	Typical Applications
	Absolute									
	MS5534C	SMD	2.2 - 3.6	10 - 1100 mbar	-40 to +125°C	0.1	±1.5	TE Proprietary	9 x 9 x 4.3	Mobile Altimeter/Barometers, Weather Control Systems, Multifunction Watches, GPS Receivers
	MS5535x	SMD	2.2 - 3.6	14, 30 bar	-40 to +125°C	1.2, 3	-400 to 500, -160 to +200	TE Proprietary	9 x 9 x 4.3	Diving Computers, Mobile Water Depth
	MS5540C	SMD	2.2 - 3.6	10 - 1100 mbar	-40 to +85°C	0.1	±1.5	TE Proprietary	6.2 x 6.4 x 2.9	Mobile Altimeter/Barometer Systems, Multifunction Watches, GPS Receivers, Weather Control Systems
	MS5541x	SMD	2.2 - 3.6	14, 30 bar	-40 to +85°C	1.2, 3	+300	TE Proprietary	6.2 x 6.4 x 2.9	Diving Computers, Multifunction Watches, Mobile Water Measurements

ANALOG OUTPUT BOARD MOUNT PRESSURE SENSORS

mV Output Pressure Sensors


	Product	Package	Supply Voltage	Pressure Range	Operating Temperature [°C]	Output/Span [mV]	Accuracy	Size [mm]	Feature	Typical Application
Absolute - Uncompensated										
	MS52xx	SMD	5 V, 20 V	1, 12 bar	-40 to +125°C	150, 240	±0.05/0.15% FS	7.6 x 7.6 x 4.3	Voltage Excitation	Altimeters, Barometers, Engine Controls, Tire Pressure
	MS52xx C&T	SMD	5 V, 20 V	1, 4, 7 bar	-40 to +125°C	240, 225, 392	±0.15% FS	7.6 x 7.6 x 4.3	Voltage Excitation	Altimeters, Barometers, Engine Controls
	MS54xx	SMD	5 V, 20 V	1, 7, 12 bar	-40 to +125°C	150, 240, 310, 392	±0.05% or ±0.2%	6.2 x 6.4 x 2.9	Voltage Excitation	Brake Systems, Engine Management, Swim Watches, Dive Computers
Gauge - Uncompensated										
	MS5201-XD	SMD	5 V, 20 V	1 bar	-40 to +125°C	150, 240	±0.05/0.15% FS	7.6 x 7.6 x 8.5	Voltage Excitation	Medical Devices, Pneumatic Controls

Amplified Ratiometric Analog Output Pressure Sensors

	Product	Package	Supply Voltage	Pressure Range	Operating Temperature [°C]	Output/Span [Vdc]	Accuracy	Size [mm]	Feature	Typical Application
Differential, Gauge										
	MS4515	8 pin DIL	3.3, 5 V	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85°C	10 - 90% 5 - 95%	±0.25% Span	12.5 x 9.9	Barbed Pressure Ports	Blocked Filter Detection, Medical Devices
Absolute, Compound, Differential, Gauge, Vacuum										
	MS4525	8 pin DIL	3.3, 5 V	1, 2, 5, 15, 30, 50, 100, 150 psi	-25 to +105°C	10 - 90%, 5 - 95%	±0.25% Span	12.5 x 9.9	Barbed Pressure Ports	Factory Automation, Medical Devices







DIGITAL OUTPUT BOARD MOUNT PRESSURE SENSORS

24-Bit, Ultra-Low Power, Pressure, Temperature and Humidity (100% RH) Sensors



	Product	Package	Supply Voltage	Pressure Range	Operating Temperature [°C]	Total Error [%FS]	Accuracy [%FS]	Digital Interface Protocol	Size [mm]	Typical Applications
	Absolute									
	MS8607	SMD	1.5 - 3.6 V	2 bar, 100% RH	-40 to +85°C	0.016	±4.0	I ² C	5 x 3 x 1	Smart Phones, Tablets, HVACR, Weather Station, Home Appliances, Humidifiers

STANDARD SIZE BOARD MOUNT PRESSURE SENSORS

Performance Line Board Mount Pressure Sensors

	Product Family	Package	Supply Voltage	Pressure Range	Compensated Temperature [°C]	Output	TEB [%FS]	Size[mm]	Feature	Typical Application
	SM1000	SMD	5V / 3.3 V	15 - 30 Psi	-20 - 85°C	Analog, I ² C	1%	SO16, SO10	Cost Effective SMD Package for High Volume Applications and Automated Manufacturing.	Industrial, Medical
	SM4000	SMD	5V / 3.3 V	2.5 - 14.9 Psi	-20 - 85°C	Analog, I ² C	1%	SO16, SO10		Industrial, Medical
	SM5000	SMD	5V / 3.3 V	0.8 - 2.49 Psi	-20 - 85°C	Analog, I ² C	1%	SO16		Industrial, Medical
	SM6000	SMD	5V / 3.3 V	0.3 - 0.79 Psi	-20 - 85°C	Analog, I ² C	1%	SO16		Industrial, Medical
	SM7000	SMD	5V / 3.3 V	0.07 - 0.29 Psi	-20 - 85°C	Analog, I ² C	1%	SO16		Industrial, Medical
	SM9000	SMD	5V / 3.3 V	125 - 600Pa	-20 - 85°C	Analog, I ² C	1% after autozero	SO16		Air Flow Measurement, HVACR, Medical Devices

STANDARD SIZE BOARD MOUNT PRESSURE SENSORS

Ultra Low Differential Pressure Sensors										
	Product Family	Package	Supply Voltage	Pressure Range	Compensated Temperature [°C]	Output	TEB [%FS]	Size[mm]	Feature	Typical Application
	LMI	SMT	5V / 3.3 V	25 - 5000Pa	0 - 70°C	Analog, I ² C	typ. 0.5% @ 25°C	< 18 x 13 x 10	Thermal Flow Principle for Superior Ultra-Low Pressure Measurement. High Immunity to Dust, Particles and Humidity	Air Flow Measurement, HVACR, Medical Devices
	LDE	THT / SMT	5V / 3.3 V	25 - 500Pa	0 - 70°C	Analog, SPI	typ. 0.5% @ 25°C	< 19 x 19 x 11	Thermal Flow Principle for Superior Ultra-Low Pressure Measurement. High Immunity to Dust, Particles and Humidity	Air Flow Measurement, HVACR, Medical Devices

te.com

TE Connectivity, TE connectivity (logo) and TE are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. Other products, logos and company names mentioned herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2023 TE Connectivity Ltd. All Rights Reserved.

12/23 Original